

Catifa 46


Design by Lievore Altherr Molina, 2012

Art. 0450

Chair with four-leg steel frame, available in chromed, brushed or powdercoated version. Polypropylene shell with cushion upholstered in fabric, leather, coated fabric or customer's own material applied to the seat surface. Upon request armrests are offered in the same finishes of the base, also upholstered.



Dimensions *



* File CAD 2D - 3D available for download at www.arper.com

Frame Base



Shell

Polypropylene



- with stacking pad, without tools up to 8 units
- with stacking pad, with trolley up to 8 units
- with link: with stacking pad, without tools up to 8 units
- with link: with stacking pad, with trolley up to 8 units

- leather / coated fabric: with stacking pad, without tools up to 5 units
- leather / coated fabric: with stacking pad, with trolley up to 5 units
- leather / coated fabric with link: with stacking pad, without tools up to 5 units
- leather / coated fabric with link: with stacking pad, with trolley up to 5 units

- with arms (BV version only): with stacking pad, without tools up to 5 units
- with arms (BV version only): with stacking pad, with trolley up to 5 units
- with arms (BV version only) with link: with stacking pad, without tools up to 5 units
- with arms (BV version only) with link: with stacking pad, with trolley up to 5 units

arper

info@arper.com

www.arper.com

Catifa 46

Design by Lievore Altherr Molina, 2012

Accessories:



Link Art. 0258



Stacking protection pad with link Art. 0277



Stacking protection pad Art. 0499



Trolley Art. 0760



Set of glides Art. 2015



Movable link Art. 2073



Armrests BV



Armrests BV brushed stainless steel



Armrests CI - only pad

arper

SHIPMENT DETAILS

Art.0450

- 1 pz = 2 - kg 10,6/ m³ 0,272
- 1 pz = 3 - kg 12,9/ m³ 0,3
- 4 pz = 2 - kg 35,44/ m³ 0,368
- 4 pz = 3 - kg 43,12/ m³ 0,404

RESISTANCE TEST

- EN 1728:2012 - EN 16139:2013 6.15
- EN 1728:2012 - EN 16139:2013 6.17
- EN 1728:2012 - EN 16139:2013 6.4
- TUV GS (EN16139)
- EN 1728:2012 - EN 16139:2013 6.18
- EN 1728:2012 - EN 16139:2013 6.5

ENVIRONMENTAL CERTIFICATIONS



TECHNICAL SPECIFICATIONS

Art.0450

- COL requirement m² 0.48
- H 140 cm. COM Meterage m 0.59

FIRE RETARDANT TEST

- Classe 1IM Omologazione Italia Divina MD Kvadrat Divina Melange 3 Kvadrat Divina 3 Kvadrat Elmosoft Field Kvadrat Hallingdal 65 Kvadrat Revive 1 Kvadrat Remix 3 Kvadrat Coated fabric Valencia Spradling

www.arper.com info@arper.com