
Design by Lievore Altherr Molina, 2004

Art. 0251

Chair with four-leg frame, available in chromed or powdercoated steel, or brushed stainless steel versions. The shell is available in single-colour polypropylene, bi-colour polypropylene or covered in hard leather without padding. Versions with polypropylene shell and powdercoated or brushed base can be used outdoor. Upon request armrests are offered in the same finishes of the base, also with pad.




Dimensions *



* File CAD 2D - 3D available for download at www.arper.com

arper



Shell

Polypropylene



- without tools up to 10 units
- with trolley up to 20 units
- with link: without tools up to 10 units
- with link: with trolley up to 14 units
- CT: with stacking pad, without tools up to 5 units
- CT: with stacking pad, with trolley up to 5 units
- CT with link: with stacking pad, without tools up to 5 units
- CT with link: with stacking pad, with trolley up to 5 units
- with arms (BV version only): without tools up to 5 units
- with arms (BV version only): with trolley up to 5 units
- with arms (BV version only) with link: without tools up to 5 units
- with arms (BV version only) with link: with trolley up to 5 units

www.arper.com

Catifa 46

Design by Lievore Altherr Molina, 2004

Accessories:



Link Art. 0258



Stacking protection pad with link Art. 0260



Cushion Art. 0261



Stacking protection pad Art.

Removable cover Art. 0309



Trolley Art. 0760



Set of glides Art. 2015



Movable link Art. 2073



Armrests BV



Armrests BV brushed stainless steel



Armrests CV - pad (only for PO)

SHIPMENT DETAILS

Art.0251

1 pz = 2 $\frac{1}{100}$ - kg 7,9/ m³ 0,247 1 pz = 3 | kg 1,3/111 0,247 1 pz = 3 | kg 10,2/ m³ 0,271 4 pz = 2 | kg 28/ m³ 0,322 4 pz = 3 appr - kg 35,7/ m³ 0,34

RESISTANCE TEST

- EN 1728:2012 EN 16139:2013 6.15
 EN 1728:2012 EN 16139:2013 6.4
 EN 1728:2012 EN 16139:2013 6.17
 TUV GS (EN16139)

- EN 1728:2012 EN 16139:2013 6.16
 EN 1728:2012 EN 16139:2013 6.5
 EN 1728:2012 EN 16139:2013 6.18

Outdoor: only for PO, V12, V13, V39, V48, V53, V54, V55, V56, V57 Outdoor powdercoated *Classe 1, 2, 1IM: fire retardant version available with surcharge and eventual minimum batch

FIRE RETARDANT TEST

TECHNICAL SPECIFICATIONS