Catifa 46


Design by Lievore Altherr Molina, 2004

Art. 0253

Chair with four-leg steel frame, available in chromed, brushed or powdercoated version. The shell is upholstered in leather, coated fabric, fabric or customer's own material. Line detail stitching. Upon request armrests are offered in the same finishes of the base.



Dimensions *



* File CAD 2D - 3D available for download at www.arper.com



Shell

- with stacking pad, without tools up to 8 units
- with stacking pad, with trolley up to 8 units
- with link: with stacking pad, without tools up to 8 units
- with link: with stacking pad, with trolley up to 8 units
- leather / coated fabric: with stacking pad, without tools up to 5 units
- leather / coated fabric: with stacking pad, with trolley up to 5 units
 leather / coated fabric with link: with stacking pad, without tools up to 5 units
- leather / coated fabric with link: with stacking pad, with trolley up to 5 units
- with arms (BV version only): with stacking pad, without tools up to 5 units
- with arms (BV version only): with stacking pad, with trolley up to 5 units
- with arms (BV version only) with link: with stacking pad, without tools up to 5
- with arms (BV version only) with link: with stacking pad, with trolley up to 5 units

Catifa 46

Design by Lievore Altherr Molina, 2004

Accessories:



Link Art. 0258



Stacking protection pad with link Art. 0277



Stacking protection pad Art.



Trolley Art. 0760



Set of glides Art. 2015



Movable link Art. 2073



Armrests BV



Armrests BV brushed stainless steel



Armrests CI - only pad

SHIPMENT DETAILS

Art.0253

1 pz = 2 $\frac{1}{100}$ - kg 9,2/ m³ 0,265 1 pz = 3 apper - kg 11,5/ m³ 0,293

4 pz = 2 February - kg 34/ m³ 0,36

4 pz = 3 apar - kg 41,7/ m³ 0,396

RESISTANCE TEST

EN 1728:2012 - EN 16139:2013 6.15
 EN 1728:2012 - EN 16139:2013 6.4
 EN 1728:2012 - EN 16139:2013 6.17
 TUV GS (EN16139)

EN 1728:2012 - EN 16139:2013 6.16
EN 1728:2012 - EN 16139:2013 6.5
EN 1728:2012 - EN 16139:2013 6.18

ENVIRONMENTAL CERTIFICATIONS





TECHNICAL SPECIFICATIONS

Art.0253

COL requirement m² 1.67 H 140 cm. COM Meterage m 1.1
*Classe 1, 2, 1IM: fire retardant version available with surcharge and eventual minimum batch

FIRE RETARDANT TEST

Classe 1 Omologazione Italia Polipropilene • M2 Polipropilene